



Lube Control Pty Ltd
Providing lubrication solutions!

Unit 5/53 Norfolk Rd,
 Marion, SA 5043





t: (08) 8298 5563
 f: (08) 8298 6253
 e: info@lubecontrol.com.au





AIR OPERATED OIL DRUM PUMPS TO SUIT 20L, 60L, 205, 1000L, WALL MOUNT & BULK TANKS

20L AIR OPERATED DRUM PUMPS



<p>1:1 Air Op Oil Pump 20L, 62 LPM Part Number: 351120</p> <ul style="list-style-type: none"> • 1:1 ratio air motor for high volume transfer from a 20L drum. • Delivers up to 62 LPM free flow. Used to transfer light to medium viscosity oils over low distances at high volume delivery rates. 	
<p>5:1 Air Op Oil Pump 20L, 35 LPM Part Number: 347120</p> <ul style="list-style-type: none"> • 5:1 ratio air motor for heavy oils or pumping over distance from a 20 litre drum. • Delivers up to 35 LPM free flow. 	
<p>1:1 Air Op Oil Pump 20L, 53 LPM Part Number: 7216-20</p> <ul style="list-style-type: none"> • Alemite USA made. • Delivers up to 53 LPM with light fluids. • Material Inlet/outlet: 1-1/2" / 1". • Air inlet: 1/4". 	
<p>4:1 Air Op Oil Pump 20L, 12 LPM Part Number: 8560-A4-20</p> <ul style="list-style-type: none"> • Alemite Standard "H" 4:1 ratio air motor - heavy duty. • Delivers up to 12 LPM. • The air motor is 2-7/16" diameter. • Air inlet 1/4" NPTF(f). • Material inlet: 1-1/2" NPTF(f) Outlet: 3/8" NPTF(f) 	

60 and 205L AIR OPERATED DRUM PUMPS




<p>3:1 Air Op Oil Pump 60/205L, 45 LPM Part Number: 341100</p> <ul style="list-style-type: none"> • Double acting pump for medium size installations. Pump tube diameter: 52mm. Air piston diam: 90mm • Air piston stroke: 100mm. Max free flow: 45 LPM • Min air pressure: 42psi. Max air pressure: 140psi • Air inlet: 3/8" BSPT (F). Fluid outlet: 3/4" BSP (F) • Weight: 9.6kg's 	
<p>3:1 Ratio Oil Transfer Drum Pumps Part Number: 354100 / 353110</p> <p>For medium size systems which involve hose reels and metered oil dispensing guns without simultaneous operation, we recommend using the 354100 3:1 ratio oil pump.</p> <ul style="list-style-type: none"> ▪ Flow rates of up to 30 litres per minute ▪ Air inlet pressures between 40 & 145psi ▪ Fluid outlets of 1/2" BSP (f) ▪ Air inlet of 1/4" BSP (f) ▪ Suits 205 litre drums ▪ Individual spare parts and service repair kit readily available ▪ Part Number 353110 as above but suitable for bulk tank applications 	
<p>5:1 Ratio Oil Transfer Drum Pump Part Number: 348100</p> <p>The 348100 5:1 ratio oil transfer pump is designed to be used in 205 litre drums. With a maximum free flow delivery of 35LPM, the 348100 is the ideal pump for dispensing high viscosity lubricants in car dealerships, truck or bus workshops. The powerful 90mm diameter air motor with a 100mm stroke will provide you with years of trouble free operation, even in the most arduous and challenging operating conditions.</p> <ul style="list-style-type: none"> ▪ Can service up to 8 reels ▪ Maximum free flow of up to 35LPM ▪ 3/4" BSP (f) fluid outlet ▪ 3/8" BSP (f) air inlet ▪ Suits 205 litre drums ▪ Part Number 347100 as above but suitable for bulk tank applications 	
<p>1:1 Air Op Oil Pump 60/205L, 60 LPM Part Number: 9917-B</p> <ul style="list-style-type: none"> • Alemite USA made. • 1:1 high volume RAM air motor. • Delivers up to 60 LPM free flow. • Material inlet / outlet: 1-1/2" NPTF(f) / 1/2" NPTF(f). 	

<p>3:1 Air Op Oil Pump 60/205L, 40 LPM Part Number: 9919-B</p> <ul style="list-style-type: none"> • Alemite USA made. • 3:1 ratio RAM High Volume air motor. • Delivery up to 40 LPM free flow. • Ideal for heavier gear oils or when high flow rates are required often over distance. • Material inlet / outlet: 1-1/2" NPTF(f) / 1/2" NPTF(f). 	
<p>4:1 Air Op Oil Pump 60/205L, 12 LPM Part Number: 8569-B</p> <ul style="list-style-type: none"> • Alemite Standard "H" 4:1 ratio air motor - heavy duty. • Delivers up to 12 LPM. • The air motor is 2-7/16" diameter. • Air inlet 1/4" NPTF(f). • Material inlet: 1-1/2" NPTF(f) Outlet: 3/8" NPTF(f). 	
<p>Alemite 5:1 Ratio Oil Transfer Drum Pump Part Number: 9969-B</p> <p>The Alemite RAM 9969-B 5:1 ratio oil transfer drum pump meets and surpasses your oil dispensing needs with exclusive design and construction features that are unmatched in the industry.</p> <ul style="list-style-type: none"> ▪ Spool valve design ensures fewer pump failures ▪ Modular design maximizes operating time ▪ Delivery rates up to 28LPM ▪ Quiet operation cuts noise levels by up to 30% ▪ Can service up to 3 reels ▪ 1/2" NPT (f) fluid outlet ▪ Suits 205 litre drums ▪ Material inlet / outlet: 1-1/2" NPTF(f) / 1/2" NPTF(f). ▪ Part Number 9968 as above but suitable for bulk tank applications 	
<p>10:1 Air Op Oil Pump, 60/205L, 15 LPM Part Number: 9971-B</p> <ul style="list-style-type: none"> • Alemite USA made. • 10:1 ratio RAM air motor. • Delivers up to 15 LPM. • Used for heavier weight oils and light greases or over long delivery distances. • Material inlet / outlet: 1" NPTF(f) / 3/8" NPTF(f). 	

STUB PUMPS TO SUIT 1000L IBC BINS OR WALL MOUNT

<p>1:1 Ratio Air Operated Oil Stub Pump Part Number: 352120</p> <ul style="list-style-type: none">▪ One piece molded & precision machined cylinder encompasses the pump tube, air cylinder and outlet port▪ Designed for wall mounting and facilitates clean & efficient oil transfer without the risk of contamination hazards▪ Flow rates of up to 50 litres per minute▪ Air inlet pressures between 43 and 115 PSI▪ Dry suction lift of 6.5 metres▪ Air inlet of 1/4" NPT (F)▪ Fluid inlet of 1" BSP (F)▪ Fluid outlet of 3/4" NPT (F)	
<p>3:1 Ratio Oil Stub Pump Part Number: 353120</p> <p>The samoa 353120 is an air operated 3:1 ratio stub pump designed for wall mounting and is ideal for dispensing lubricants from mobile units or in small to medium size distribution systems that include pipelines, hose reels and metered valves with no simultaneous operation outlets</p> <ul style="list-style-type: none">▪ Flow rates of up to 35 litres per minute▪ Air inlet pressures between 43 & 115psi▪ Fluid outlet of 3/4" NPT (f)▪ Air inlet of 1/4" NPT (f)▪ Dry suction lift of 6.5 metres▪ Maximum fluid pressure of 340psi	

BULK TANK OIL PUMPS

<p>Alemite Bulk Tank Oil Pump Part Number: 9968</p> <ul style="list-style-type: none">▪ Spool valve design ensures fewer pump failures▪ Modular design maximizes operating time▪ 5:1 ratio pump▪ Delivery rates up to 28LPM▪ Made in the USA	 A vertical, cylindrical oil pump with a red and silver finish. It features a spool valve design and a CE certification mark on the side.
<p>Alemite 6:1 Ratio Oil Transfer Tank Pump Part Number: 7783-C4</p> <ul style="list-style-type: none">▪ Rugged 4 x 1/4" air motor ensures trouble free operation in even the harshest of operating environments▪ Delivery lengths up to 100m▪ Can service up to 6 reels▪ Maximum free flow of 38LPM▪ 3/4" NPT (f) air inlet▪ 1/2" NPT (f) material outlet▪ Fast and efficient oil transfer guaranteed	 A vertical, cylindrical oil pump with a red and silver finish. It has a rugged design with a 4 x 1/4" air motor and various ports for air and material.
<p>10:1 Ratio Oil Transfer Pump Part Number: 343000</p> <ul style="list-style-type: none">▪ Double acting oil pump suitable for dispensing lubricants in large installations including multiple dispensing points with simultaneous operations▪ Flow rates of up to 40LPM▪ 10:1 ratio▪ Maximum oil pressure of 1,400psi▪ 1/2" BSP (f) air inlet▪ 3/4" BSP (f) material outlet	 A vertical, cylindrical oil pump with a white and silver finish. It features a double-acting design and a SAMCO logo on the side.