



SYNTHETIC HIGH TEMPERATURE LUBRICANTS

ADDINOL Chain Lube XHT 50 Spray ADDINOL Chain Lube XHT 250 Spray ADDINOL Chain Lube XHT 3000 Spray

APPLICATION

ADDINOL Chain Lube XHT Sprays are primarily used to lubricate conveyor chains in high temperature applications such as drying ovens, tender frames, lacquering paint lines, baking ovens, slides, wire ropes and other such devices. Main application industries are automotive, machine building, textile industry, glass and wool production and similar equipment at temperatures up to 250°C.

ADDINOL Chain Lube XHT Sprays are available in three different viscosity ranges making it possible to choose the best solution for every application. A very low evaporation rate and high thermal stability of ADDINOL Chain Lube XHT Sprays enable very economic application.

The quantity of oil applied depends on type of chain and environmental conditions, these should be agreed upon with equipment manufacturer or local supplier.

Instruction for application:

- Shake can well before use. Apply thinly and evenly. Keep spray head approximately 300mm away from surface.
- Product foams on surface until it has penetrated into the friction point.
- Follow the safety instructions as per can and Material Safety Data Sheet.
- Ask your local distributor for additional information.

DELIVERY

500ml spray cans

TYPICAL PARAMETERS

(for product without aerosol propellant)

Product Chain Lube	Viscosity (mm ² /s)			Density (kg/m ³)	Flash point (°C)	Pour Point (°C)	Volatility (%)
	at +40°C	at +100°C	at +200°C	at +15°C			
XHT 50	49	7.6	1.85	970	260	-33	2
XHT 250	255	24.5	4.0	965	290	-39	1.5
XHT 3000	3000	170	16.0	965	300	-15	<1

PRODUCT DESCRIPTION

ADDINOL Chain Lube XHT Sprays are fully synthetic high performance lubricants for high temperature applications. These oils are based on special complex esters with high thermal stability and very low evaporation loss.

ADDINOL XHT Sprays feature:

- **Water resistance**
- **Outstanding ageing resistance and corrosion protection.**
- **Extreme thermal oxidative stability with very low tendency to form deposits and low volatility.**
- **Excellent wear protection under high and changing loads (stick slip prevention).**
- **Superior adhesion, penetration and load bearing capacity.**
- **Free of silicone additives**



Imported by **Lube Control**
www.lubecontrol.com.au
883 Ackland Hill Rd, Coromandel East, SA 5157
Tel: 08 8370 5133, Fax: 08 8370 5551