



SPECIAL GREASE

ADDINOL CONTACT GREASE EL – K2

APPLICATION

ADDINOL Contact grease EL – K2 is used as an isolator and protects against corrosion and wear when in contact with copper containing materials as found in manufacturing, railway vehicles, construction machinery and shipping. The product prevents electrostatic charge developing.

ADDINOL Contact grease EL – K2 is a water resistant lubricating grease and prevents unwanted discharge in damp or wet environments.

Operating temperature from -30°C to +85°C.

ADDINOL Contact grease EL – K2 is used in particular in motor cars for lubrication and contact protect of power and control switches. It is also suitable for boards and potentiometers.

Available in 1kg drums.

PRODUCT DESCRIPTION

▪ **ADDINOL Contact EL-K2** is a calcium soap thickened contact and lubricating grease based on mineral oil. It is very water resistant and is very easily pumped.

▪ **Designation according to DIN 51502: M2E-30**

TYPICAL PARAMETERS

ADDINOL LONGLIFE HP 2	Units	Value	Method
Consistency/NLGI	-	2	-
Dropping point	°C	>100	DIN ISO 2176
Breakdown voltage	KV	19	DIN 57370/DIN VDE0370
Worked Penetration	0.1mm	265-295	DIN ISO 2137
BASE OIL			
Type		Mineral oil	
Kinematic viscosity at 40 °C	mm ² /s	52	DIN 51562



Imported by:

Lube Control
883 Ackland Hill Rd
Coromandel East, SA 5157
Tel: 08 8370 5133, Fax: 08 8370 5551

Distributed by: