



LIQUID GREASE

ADDINOL LIQUID GREASE SGR 00

APPLICATION

ADDINOL Liquid grease SGR 00 is used to lubricate gearboxes under server operating conditions. It boasts extended component life and energy savings due to surface improvements on gears.

It can be used in leaking gearboxes to inhibit oil seepage. Under certain conditions this product can be a life time fill (please see local supplier).

ADDINOL Liquid grease SGR 00 has excellent pump ability in centralised lubrication system where heavier consistencies fail.

ADDINOL Liquid grease SGR 00 is great for gears without oil tight enclosures, tooth couplings and roller bearings.

ADDINOL Liquid grease SGR 00 is compatible with conventional sealing material and non ferrous metals.

PRODUCT DESCRIPTION

ADDINOL Liquid grease SGR 00 is a combination of mineral oil, organic thickener, EP additives and corrosion inhibiting substances to produce a semi liquid homogenous grease.

ADDINOL Liquid grease SGR 00 features:

- **Excellent load carrying capacity**
- **Outstanding rust protection**
- **Easily pumpable in centralise lubrication systems**
- **Resistance to hot and cold water**
- **Temperature range -35°C to +100°C**

Designation in accordance with DIN 51502: GP00G-30

DELIVERY

5kg and 20kg pails

TYPICAL PARAMETERS

ADDINOL LIQUID GREASE SGR 00	Units	Value	Method
Consistency class	°C	00	DIN 51818
Worked penetration	0.1mm	400-430	DIN ISO 2137
VKA – welding point	N	2600	51530, T. 4
Load limits	N	18000	

BASE OIL		Mineral oil	
Kinematic viscosity at +40°C	mm ² /s	140	DIN 51562
Pour point	°C	-18	DIN ISO 3016



Imported by:

Lube Control
883 Ackland Hill Rd
Coromandel East, SA 5157
Tel: 08 8370 5133, Fax: 08 8370 5551

Distributed by: