



SPECIAL HIGH PERFORMANCE GEARBOX OILS

ADDINOL ECO GEAR 68M, 100M, 150M, 220M 320M, 460M & 680M

APPLICATION

ADDINOL Eco Gear M can be used for nearly all types of enclosed industrial gears.

Preferably used in gearboxes with low to high loads, dynamically changing drives and thermally critical conditions in a vast temperature range.

Additional uses:

- For all types of sliding and rolling bearings
- Gear couplings, slide ways, joints and circulating systems.

The recommend use of ADDINOL Eco Gear M in Flender gears is approved.

The viscosity is mainly determined by the particular application, operating conditions and manufacturers recommendation.

ADDINOL Eco Gear M oils are compatible with standard sealing materials. They are solid free and can be used in conjunction with filters or centrifuge.

DELIVERY

20L and 205L Drums

PRODUCT DESCRIPTION

ADDINOL Eco Gear M high performance gearbox oils are produced on the basis of a selected composition and specially created additive system - Surftec.

ADDINOL Eco Gear M oils Feature:

- **Prevention of grey staining (micro pitting) and pittings.**
- **Outstanding wear protection.**
- **Reliable corrosion resistance for steel and non ferrous metals.**
- **Increased lubricant life resulting in reduction of waste oil disposal and labour cost.**
- **Decrease in friction contributing to reduction in noise and oil sump temperatures, increase component performance and energy savings.**
- **Re smoothening of extremely strained surfaces.**

Addinol Eco Gear M Oils meet DIN 51517-3 and ISO12925-1 standards.

TYPICAL PARAMETERS

Product ADDINOL (ISO-VG)	Viscosity (mm ² /s)		Density (kg/m ³)	Flash point (°C)	Pour Point (°C)	Grey Flecking Test FVA No. 54	FZG Test A/16,6/120 Power Stage
	at +40°C	at + 100°C					
Eco Gear 68M	65	8	875	230	-20	>10	>12
Eco Gear 100M	100	11	880	230	-21	>10	>12
Eco Gear 150M	145	15	885	230	-18	>10	>12
Eco Gear 220M	215	19	890	235	-15	>10	>12
Eco Gear 320M	315	26	900	245	-15	>10	>12
Eco Gear 460M	460	32	913	245	-12	>10	>12
Eco Gear 680M	655	40	912	230	-9	>10	>12



**LUBE
Control**

Marketed by:

Lube Control
U5 53 Norfolk Rd
Marion SA 5043
Tel: 08 8298 5563, Fax: 08 8298 6253

Distributed by: