



www.eal.com.au

**ADHESIVES, SEALANTS & LUBRICANTS
PRODUCT CATALOGUE
ENGINEERING ADHESIVES & LUBRICANTS (AUST) PTY LTD
P.O. Box 863, Ashmore City, Queensland 4214
Tel: (07) 5531-4242 Fax: (07) 5531-4243**



**LUBE
Control**

Lube Control Pty Ltd
Providing lubrication solutions!

Unit 5/53 Norfolk Rd,
Marion, SA 5043
t: (08) 8298 5563
f: (08) 8298 6253
e: info@lubecontrol.com.au

www.lubecontrol.com.au

**CYBERBOND
ADHESIVES AND SEALANTS**

THREADLOCKING COMPOUNDS

7222 SCREWLOCK - 10ml / 50ml / 250ml
Designed for adjustment of set screws, small diameter or long engagement length fasteners where easy disassembly is required.

7243 NUTLOCK - 10ml / 50ml / 250ml
Prevents loosening of threaded fasteners. Suitable for pump and motor mounting bolts, engine rocker nuts or equipment housing screws. Designed for disassembly with normal hand tools when servicing is required.

7262 STUDLOCK - 10ml / 50ml / 250ml
Prevents loosening of threaded fasteners. Designed for permanent locking and sealing in heavy duty applications such as transmission bolts and construction equipment.

7277 HEAVY DUTY - 50ml / 250ml
Designed for permanent locking and sealing of threaded fasteners in heavy duty applications that use larger diameter bolts and nuts.

7290 PENETRATING - 50ml / 250ml
Designed for preassembled parts such as carburetor screws and instrumentation fasteners where positioning is required before application of the adhesive.

PUMP GEL THREADLOCKER Outperforms the leading gel and stick products in the marketplace. Stays where it is applied. Will not run. Easy to use self-metering pump eliminates waste.

TT44 - 39ml Gel Pump
Medium Strength Gel Threadlocker. Ideal for all 6mm to 25mm nut and bolt assemblies. Can be disassembled with normal hand tools.

TT62 - 39ml Gel Pump
High Strength Gel Threadlocker. Ideal for all 6mm to 25mm nut and bolt assemblies. Resists heavy shock and vibration. Use for permanent assemblies where future disassembly is not likely.

RETAINING COMPOUNDS

7609 RETAINING COMPOUND - High Strength, Low Viscosity - 10ml / 50ml / 250ml
Used to bond cylindrical parts such as pulleys, gears, rotors and shafts as well as to secure bushings, bearings and housing plugs. Augments press fits.

7620 RETAINING COMPOUND - High Strength, Extra High Viscosity - 10ml / 50ml / 250ml
Maximum gap-filling ability. Designed to bond cylindrical parts in high temperature applications such as pump housing sleeves and transmission bearings.

7640 RETAINING COMPOUND - High Strength, Medium Viscosity - 10ml / 50ml / 250ml
Used to retain pulleys, gears, rotors and shafts in demanding vibrational and high friction applications. Develops very high strength and temperature resistance.

7680 RETAINING COMPOUND - High Strength, High Viscosity - 10ml / 50ml / 250ml
Designed to bond cylindrical parts such as bushes, bearings, pulleys, gears, rotors and sleeves. Excellent bonding versatility to augment the installation of replacement bearings.

THREAD SEALANTS

7567 PTFE PIPE SEALANT - 50ml / 250ml
High performance anaerobic sealant designed for straight and tapered metal pipe threads. Prevents galling on stainless steel, aluminium and other metal threads and fittings. Lubricates and seals to prevent leaks.

7569 HYDRAULIC SEALANT - 10ml / 50ml / 250ml
Designed for locking and sealing straight and tapered metal threads such as hydraulic and pneumatic fittings. Excellent chemical resistance.

7577 HIGH PRESSURE PIPE SEALANT - 50ml / 250ml

Designed for locking and sealing all types of specialty metal fittings. Prevents loosening and leakage associated with shock and vibration. Instant seal on low pressure systems.

FLANGE SEALANTS

7510 FLANGE SEALANT - 50ml / 250ml

Designed for sealing components operating continuously up to 200°C. Has the ability to bridge small gaps provided the parts are rigid. Resistant to fuels, most solvents, transmission fluid and oil.

7515 FLANGE SEALANT - 50ml / 300ml

Designed for sealing and gasketing close fitting joints between rigid metal faces and flanges. For use on crankcases, gearbox covers, pump couplings & thermostats etc.

7518 FLANGE SEALANT - 50ml / 300ml

Designed to seal close fitting joints between metal faces and flanges. Used as a form-in-place gasket material on rigid flanged connections such as gear boxes and engine casings.

7587 BLUE RTV SILICONE - 300g cartridge

Will not foul oxygen sensors. Makes reliable form-in-place gaskets. Used for sealing: valve covers, oil pans, timing covers, water pumps, thermostat housings, transmission pans.

7599 GREY RTV SILICONE - 300g cartridge

Makes reliable form-in-place gaskets. Sensor safe and outstanding oil resistance. Used for sealing: valve covers, oil pans, intake manifold end seals, timing covers, water pumps, thermostat housings.

7596 HIGH TEMP RED SILICONE - 300g cartridge

High performance RTV Silicone adhesive/sealant designed for form-in-place gaskets and other high temperature industrial applications. Used for sealing and bonding applications exposed to temperatures as high as 350°C.

CLEANER, ACTIVATOR

9190 ACTIVATOR - 175g aerosol

Recommended for large gaps (>0.3mm), on some inactive metals and in cold condition (<5°C). The activator is applied before application of the adhesive to ensure complete curing.

9999 CLEANER - 175g aerosol / 400g aerosol

An ozone friendly universal cleaner and degreaser for use prior to the application of Cyberbond adhesives and sealants. Rapid drying and leaves no residue.

INSTANT ADHESIVES

2000 INSTANT ADHESIVE - 20g / 50g / 500g

Penetrates by capillary action. Designed for bonding all types of preassembled parts.

2005 INSTANT ADHESIVE - 20g / 50g / 500g

A fast setting, low viscosity adhesive suitable for general purpose applications on metal, rubber and plastic.

2008 INSTANT ADHESIVE - 20g / 50g / 500g

Developed specifically for rubber bonding. Excellent for joining 'O' Rings and other elastomers. Highly resistant to aging, weathering and plasticized migration.

2028 INSTANT ADHESIVE - 20g / 50g / 500g

Excellent properties for plastic and rubber bonding. Medium viscosity product which offers the user improved flow control.

2040 INSTANT ADHESIVE - 20g / 50g / 500g

Developed specifically for bonding rubber to metal. Excellent properties when bonding substrates at elevated temperatures.

2077 INSTANT ADHESIVE - 20g / 50g / 500g

Developed for bonding a variety of materials such as wood, cork, leather as well as most metals, plastics and elastomers. High viscosity product with good gap-filling ability and high impact resistance.

2241 INSTANT ADHESIVE - 20g / 50g / 500g

Rubber toughened formula. Extremely flexible. Provides superior shock and thermal resistance when bonding rubber, metal and plastic.

2610 INSTANT ADHESIVE - 20g / 50g / 500g

Excellent properties for wood bonding. Surface insensitive. The ultra fast set speed is especially suitable for porous materials.

2999 INSTANT ADHESIVE - 20g

Gel like consistency. Ideal for bonding porous materials or when controlling adhesive flow is critical. Offers maximum gap filling and repositioning time.

PRIMER, D-BONDER, ACCELERATOR

9050 PRIMER - 100ml / 1 Litre

Used as a pre-applied surface treatment to increase the bond strength on difficult to bond surfaces such as polyethylene, polypropylene, EPT and silicone rubber.

9060 D-BONDER - 20ml / 500ml

Organic ester based remover for dissolving cured cyanoacrylate adhesive. Used for cleaning dosing equipment, tools etc which have been in contact with cyanoacrylate adhesive.

9190 ACCELERATOR - 175g aerosol / 1 Litre

Accelerator can be pre-applied or post applied during assembly to increase the cure speed and gap-filling ability of Cyberbond cyanoacrylate adhesives.

**HYPOXY HIGH PERFORMANCE
METAL REPAIR AND TOOL
COMPOUNDS**

RETAIL PRODUCTS

H-1C STRONGSTEEL - 28.4g Repair Kit (2 tubes)

STRONGSTEEL® is the best material on the market for repairing pipes, radiators, tanks and engine blocks. It hardens to a gray metallic mass and adheres soundly to almost every material except for polyethylene. STRONGSTEEL® is unaffected by water, oil and gasoline and widely used by professional tradesman worldwide.

H-3S CLEARBOND - 25ml Dual Syringe

This easy-to-use ultra strong clear adhesive is widely used for the repair of models, toys, lamps, vases, furniture, picture frames and appliances.

CLEARBOND® bonds wood, fiberglass, metals, glass, china, ceramics and most plastics (not polyethylene) and is unaffected by liquids such as water, oil, and gasoline.

H-4S CLEARFAST - 25ml Dual Syringe

Easy-to-use fast curing CLEARFAST® is ideal for model making as it hardens in thin layers. It cures at low temperatures and adheres to almost all materials except some plastics such as polyethylene.

CLEARFAST® is unaffected by gasoline, oil, and grease, but not recommended for constant exposure to water.

H-7 STEELFAST - 64g Kit (2 tubes)

Fast curing STEELFAST® is the best product available when high adhesion and strength must be combined with heavy filling or surface build-up. It hardens to a gray metallic mass and adheres to most materials but not polyethylene. STEELFAST® is ideal for the quick repair of pipes, radiators and tanks that are not constantly exposed to water.

H-45 ALUMBOND - 56.8g Kit (2 tubes)

ALUMBOND® is for similar applications as HY-POXY® STEELBOND® but where an aluminum non-rusting and non-magnetic finish is desired. ALUMBOND® was specifically formulated to be used in HVAC applications for the repair of air conditioning system components, aluminum castings, machinery and equipment.

H-55 ALUMFAST - 56.8g Kit (2 tubes)

ALUMFAST® is a fast curing repair kit used for aluminum and copper pipes, valves, models, patterns and castings. HY-POXY® ALUMFAST® can be machined, sanded, drilled and tapped which makes it a popular choice for automotive, plumbing and HVAC repairs.

H-159 STEELFAST STICK - 114g Stick

STEELFAST® Stick has infinite uses filling gaps and holes on plumbing, electrical, auto, HVAC and industrial applications as it adheres to most surfaces.

STEELFAST® Stick is an epoxy-based product that is extruded in a cylindrical form to include the hardener and resin for easy and assured no waste mixing. This easy to use product can be machined and used under water as well.

H-259 ALUMFAST STICK - 57g Stick

ALUMFAST® Stick has infinite uses filling gaps and holes on plumbing, electrical, auto, HVAC and industrial applications where a non-magnetic aluminum finish is desired. It is an epoxy-based product that is extruded in a cylindrical form to include the hardener and resin for easy and assured no waste mixing. ALUMFAST® Stick adheres to most surfaces and can be machined and used under water as well.

INDUSTRIAL PRODUCTS

H-100 STEELBOND - 454g Kit

STEELBOND® is used worldwide for general maintenance and repairing pipes, valves, engine blocks, tanks, radiators, water jackets and blowholes in castings. It's ideal for drill rigs, holding fixtures and most repairs involving steel.

H-120 STEELFAST - 454g Kit

STEELFAST® is a very fast hardening steel-filled HY-POXY®, that is widely used for emergency repairs. This product is not recommended for constant immersion or exposure to water, but for such repairs the H-120 can be used to overcome the emergency and then be covered with HY-POXY® STEELBOND®.

STEELFAST® also is recommended for repairs at low temperatures.

H-200 KLEARBOND - 454g Kit

This ultra strong clear adhesive is widely used for the repair of models, toys, lamps, vases, furniture, picture frames and appliances. KLEARBOND® bonds wood, fiberglass, metals, glass, china, ceramics and most plastics (not polyethylene) and is unaffected by liquids such as water, oil, and gasoline.

H-300 CERAMIC HARD COAT - 454g Kit RED

This high-performance brushable ceramic coating is used for sealing and protecting metal surfaces against corrosion, abrasion and harsh chemicals. It provides a very hard, smooth and glossy finish.

H-400 ALUMBOND - 454g Kit

ALUMBOND® is for similar applications as HY-POXY® STEELBOND® but where an aluminum non-rusting and non-magnetic finish is desired. ALUMBOND® was specifically formulated to be used in HVAC applications for the repair of air conditioning system components, aluminum castings, machinery and equipment.

H-450 ALUMBOND - 184g Kit

Because exact amounts of resin and hardener can be dispensed from each tube, the H-450 eliminates waste and is ideal for smaller repairs. The easy to use H-450 fits comfortably into any tool box and is extremely popular with HVAC tradesmen, plumbers and auto mechanics.

H-455 ALUMFAST - 184g Kit

ALUMFAST® is a fast curing repair kit used for aluminum and copper pipes, valves, models, patterns and castings. HY-POXY® ALUMFAST® can be machined, sanded, drilled and tapped which makes it a popular choice for automotive, plumbing and HVAC repairs.

H-500 WEAR RESISTANT PUTTY - 454g Kit

This chemical resistant filler is used worldwide for pump casings, impellers, keyways and wear plates. The self-lubricating H-500 is also great for building up machine beds, shafts and slow-speed bearings.

H-600 WET SURFACE PUTTY - 454g Kit

This specially formulated putty will adhere to a wet surface. The H-600 was originally developed for underwater repairs which make it a great tool for repairing pipes, tanks, valves and machines in highly humid environments where it is impossible to completely dry the surface in need of repair.

H-800 STAINLESS STEEL PUTTY - 454g Kit

This easy to mix and apply putty is used for repairing stainless steel piping, tanks, vats, machinery and equipment. It is very popular in the food industry especially for re-building food processing equipment.

H-900 TITANIUM PUTTY - 454g Kit

This non-rusting, chemical resistant titanium-reinforced putty is specially formulated for the heavy duty repairing and rebuilding of compound metals. It has a high compressive strength of 18,400 psi and a temperature resistance of 350° F (117° C).

CPI ADHESIVES AND SEALANTS

O.E.M. GREY SILICONE - 85g tube

Formulated for high torque Japanese engines. Non-corrosive - Sensor Safe - Low Odor, CPI O.E.M. Grey Silicone can be used on all engines. Exceeds O.E.M. specifications for resistance to oil, water, anti-freeze, greases and transmission fluids. High temperature resistance up to +650°F (+343°C).

HIGH TEMP RED SILICONE - 85g tube

Resists temperatures up to +650°F (343°C). Formulated for sensor equipped engines. Resists oil, transmission fluid, anti-freeze, water, steam and diesel fuel. Use on water pumps, valve covers, timing covers, thermostat housings and transmission pans.

BLACK SILICONE GASKET MAKER - 85g tube

A sensor safe, low volatile formula which is O.E.M. approved for engines equipped with sensors. Makes an instant leak proof gasket on all engines. Fast and easy, seals windshields, door gaskets, lights, hose connections and insulates electrical connections. Resists oil, anti-freeze, water, diesel fuel and transmission fluids.

CLEAR RTV SILICONE - 85g tube

All purpose adhesive/sealant which can be used to seal windows, windshields, lights and weather stripping. Bonds and seals glass, concrete, wood, plastic, rubber and metal. Waterproof and flexible.

SUPER PEGA SUPER GLUE - 3g tube

High performance super glue formula which sets in seconds. Works on many surfaces. Use on metal, glass, most plastics, rubber, leather, wood, fabric, ceramic, vinyl, cork and paper.

REAR VIEW MIRROR ADHESIVE

Improved formula for quicker set times. Permanently remounts mirrors to windshields. Achieves handling strength in seconds. Mirror can be mounted in 15 minutes. Easy to use.

TREBLEX LUBRICANTS INDUSTRIAL PRODUCTS & AEROSOLS

BRAKE AND PARTS CLEANER -

600ml/400g aerosol / 20L drum

A specially formulated product that does not contain chlorinated solvents. Designed to quickly and safely dissolve and remove grease, oil and contaminants from brakes, parts and slides and forklift chains.

CARBURETTOR AND THROTTLE BODY CLEANER - 400g aerosol

Specifically formulated to quickly and easily dissolve carburettor deposits inside and outside. It will remove sludge, grease, varnish, gum and dirt build up.

DRILLING & TAPPING COMPOUND - 500ml

For general drilling, tapping, punching, threading and broaching. May be used for low or hi-speed lathe work. By reducing friction it reduces cutting tool temperatures and extends tool life substantially.

HEAVY DUTY W.D. LUBE - 400g aerosol

This product provides superior lubrication outstanding penetration capabilities and moisture repellent action. Heavy Duty WD will give heavy duty anti corrosion protection.

W.D LUBE BULK - 20L drum

This is a multi purpose anti-corrosion lubricant designed to displace moisture, penetrate rusted parts, lubricate, stop squeaks, clean surfaces and protect from corrosion.

HD LANOLIN - 400g aerosol

Treblex Heavy Duty Lanolin Aerosol contains pure (USP) pharmaceutical grade lanolin with a safe high purity solvent. Heavy Duty Lanolin is a multi purpose natural product designed to lubricate and provide protective coatings to most surfaces. AQIS approved category 10, Type A food grade lubricant,

BATTERY TERMINAL PROTECTOR -

360g aerosol

Designed to give maximum protection against battery failure and maintain electrical voltage performance by protecting terminals, brackets and cables from corrosion.

SILICONE LUBE PLUS - 350g aerosol

A multi purpose premium grade silicone spray that provides a thin, colourless lubricating protective coating that may be used for simple household lubrication. Can also be used for heavy duty applications in industry, including the printing and textile industries.

TACLUBE - 400g aerosol

An exceptional lubricant with superior synthetic polymer technology that has tenacious adhesive qualities that resist fling off. The extreme pressure additives protect parts subjected to vibration and shock loading. Also contains anti-wear and anti-corrosion chemistry.

MOLY CHAIN LUBE - 400g aerosol

This product is reinforced with molybdenum disulphide an exceptionally tough lubricant with adhesive qualities limiting wear to all surfaces by reducing friction and extending component life.

OPEN GEAR LUBE - 360g aerosol

Open Gear Lube is an extreme performance lubricant containing 3% molybdenum disulphide in a blend of high load additives to give maximum protection against pitting and wear. Open Gear Lube can be used on many other applications including worm gears, crown wheels, rack and pinion and chains.

WIRE ROPE LUBE - 350g aerosol

This product is an outstanding, penetrating multi purpose wire rope lubricant with 3% molybdenum disulphide for superior lubrication and protection of cables and wire ropes. Wire Rope Lube reduces friction and wear between the wires and strands of all cables thus extending their life.

ELECTRA LUBE W.D. - 450g aerosol

This is a NON-FLAMMABLE product that helps reduce downtime and maintenance costs in all electrical equipment and improves electrical properties in all high voltage applications. Also leaves a protective coating to assist with protection from corrosion.

ELECTRA CLEAN - 420g aerosol

Electra Clean is a safe replacement for products containing carbon tetrachloride. This product has NO FLASH POINT and is NON FLAMMABLE. For use in cleaning electrical motors and electrical equipment.

CO² ELECTRICAL CONTACT CLEANER -

350g aerosol

This product is a technically superior, fast drying, non residual precision cleaning solvent. When used as directed it will quickly and safely remove contaminants from boards, switches and plugs. Ensure equipment is turned off as this formula is flammable. Use Treblex Contact cleaner NF if a non flammable product is needed.

CONTACT CLEANER N.F - 450g aerosol

This technically superior, stable, inert, high purity cleaning solvent is suitable for use in all electrical appliances. This product has NO FLASH POINT, is NON FLAMMABLE and contains no lubricants.

MARINE GUARD - 350g aerosol

A heavy duty multi purpose NON-FLAMMABLE product providing superior lubrication and heavy duty corrosion protection for metal surfaces. Will protect against damage caused by water and airborne salt spray which causes corrosion damage to all types of marine and industrial equipment.

KLEEN AIR - 180g aerosol

Effectively eliminates bacteria, fungi, moulds and viruses from the air conditioning system which cause unpleasant odours, hay fever and other allergic reactions.

PU EXPANDING FOAM - 750ml aerosol

Treblex Fire Rated Foam, Class B2

The foam dispensed from the aerosol can is moisture cured and draws humidity from the air for curing. It is an economical, convenient and effective method for installation. The product is building code compliant for fire retardation in wood frame construction. Used to seal concealed penetrations from floor to floor or room to room, forms a fireblock and a durable, airtight and water-resistant bond. Bonds to wood, drywall, metal, masonry, glass and most plastics. There is an attached straw to dispense the foam from the aerosol can, ready to use.

GREASE

LITHPLEX 2 BLUE TAC - 450g, 2.5kg, 20kg

A premium, high melting point, lithium complex grease available as NLGI 2 & 3 consistency. It is a high temperature grease and has been designed to meet the demands of the most hostile grease applications and conditions. Lithplex 2 Blue TAC grease is recommended for use in most types of automotive and industrial applications including heavy duty service where high temperatures, high loads and water spray or ingress are encountered.

LITHPLEX PURPLE - 450g, 2.5kg, 20kg

A superior, state-of-the-art, lithium complex **Extra Heavy Duty** grease. It is a high temperature, high extreme pressure (EP) grease designed to meet the demands of the most severe and hostile industrial and on/off-highway automotive applications and conditions. **Lithplex Purple** is suitable for rolling element bearings, plain bearings, chassis parts, gears and couplings. Because of its outstanding EP, corrosion and water-resistant properties it is particularly suitable where water is present such as steel mills, underground tunnelling, cement, mining, sugar and ore crushing plants.

LITHPLEX MOLYTAC EP2 - 450g, 2.5kg, 20kg

A high performance Lithium complex soap base grease with semi-synthetic base oil, EP additive system and a combination of solid lubricants. Used for lubrication of slow speed anti-friction bearings, pin and bushes, universal joints, axles, etc. It is specially designed for equipment in the Mining Industry such as excavators, haul trucks, loaders, lifts, transportation and wherever it is required for efficient protection high load with environmental conditions such as dust and water. **NOT FOR USE IN WHEEL BEARINGS OR HIGH SPEED BEARINGS.**

TREBLEX CONSUMER / AUTOMOTIVE

BARRIER CREAM - 500ml

Apply Treblex Barrier Cream containing coconut oil, lanolin and emollients prior to commencing any work in workshop areas and around the home for protection of hands.

CITRA CLEAN - 500ml

Treblex Citra Clean is a premium quality pH-neutral biodegradable hand cleaner derived from a special blend of natural orange oil, coconut oil derivatives, surface active agents, emulsifiers, skin moisturizers and emollients.

CITRAGEL PLUS - 500ml

Treblex Citra Gel Plus is a specially formulated natural based hand cleaner combined with special skin emollients, making it safe to use and highly effective.

WINDOW CLEANER - 750ml

Treblex Window Cleaner is a non streaking alcohol based cleaner and polisher suitable for all shiny surfaces including glass, mirrors, chrome, windows, stainless steel, plastics and laminex. Treblex Window Cleaner may also be used to clean motor vehicle and truck windscreens of insect residue and road grime.

TREBLE CLEAN - 750ml

Treblex Treble Clean is a pleasant fragranced general purpose cleaner suitable for many applications in both domestic and industrial environments. This product is safe for use on any hard surface and it is a non caustic formula.

VINYL REVIVER - 125ml, 750ml

Treblex Vinyl Reviver is a premium product formulated to protect, enhance and preserve all vinyl and plastic surfaces, rubber trims and tyres in all automotive, marine, transport and household applications.

WD LUBE - 1 Litre

Treblex WD Lube is a unique multi purpose anti-corrosion lubricant designed to displace moisture, penetrate rusted parts, lubricate, stop squeaks, clean surfaces and protect from corrosion.

SOLVENT DEGREASER - 1 Litre

Treblex Solvent Degreaser is a proprietary formulation containing hydrocarbon solvents, added solubilisers and surfactants to assist in the remove of a wide range of grease and soilage.

SUPERBLUE - 1 Litre

Treblex Super Blue is a specially formulated hard working superior all purpose car and truck wash. This product is a carefully blended composition of surfactants and wetting agents which will emulsify dirt and grime and hold it in suspension making it easier to rinse away. Safe to use on all types of vehicles including cars, trucks and all marine hull finishes with complete confidence.

DYNAFUEL - 250ml, 1 Litre

Treblex Dynafuel is most effective at neutralizing the harmful effects of acids in aged or high sulphur fuel, and in removing existing gums and varnish deposits from all types of engines. Can be used confidently in petrol and diesel powered engines. Contains a Biocide to effectively destroy *Cladisporum resinae* making it ideal for treating stored fuel.

EAL AEROSOLS & ANTI-SEIZE LUBRICANTS

ANTI-SPATTER - 400g aerosol

Provides a film around the weld zone allowing weld spatter to be brushed away easily. Extremely effective on all metals including mild steel, stainless steel and aluminium during the MIG welding process. Prevents weld spatter adhering to work surfaces and nozzles. Non-Flammable, non-silicone, paintable.

BLACK GAL (Satin Black Finish) - 400g aerosol

An industrial strength, anti-corrosive coating fortified with zinc which prevents rust and inhibits corrosion on ferrous metals. Typical applications include gates, fences, handrails, farm equipment, marine and boating equipment and much, much more. Dries to a low sheen, satin black finish.

BRIGHT GAL (Bright Silver Finish) - 400g aerosol

Combines the protection of zinc whilst closely matching the appearance of Hot Dip Galvanizing. Eliminates the need for a silver topcoat which is especially useful for aluminium fence and gate contractors. Typical applications include cosmetic repair of welds, handrails, fences, guardrails, pipes, heavy equipment, in fact anywhere the bright look of a hot-dipped surface is preferred.

FAST DRY ENAMEL PAINT - 350g aerosol

Premium quality, high build industrial quality spray paints designed for interior and exterior use. Typically used on industrial fittings, doors, gates, wrought iron, screens, and factory equipment, in fact anywhere that a quality finish is required. Touch dry within 10 minutes. Colours: Black Gloss, Black Matt, Signal Red, Golden Yellow, Silver, Grey Primer, White, International Orange, Ocean Blue, Brunswick Green.

PURE COPPER ANTI-SEIZE - 20g / 50g / 250g

brush-top can / 500g brush-top can / 2.5kg / 5kg / 20kg
A high temperature, corrosion resistant anti-seize and assembly lubricant designed for use on all static threaded fasteners and mechanisms. Due to its high proportion of metallic and other lubricating solids, it facilitates positive tightening and eases dismantling. Prevents seizure and galling in wet, corrosive and dirty conditions and can be used in chemical environments. It is ideally suited for use in the most severe conditions including ovens and furnaces, exhaust systems, mining, marine and automotive applications. Temperature range -30C to +1100C.

PURE NICKEL ANTI-SEIZE - 20g / 50g / 225g

brush-top tin / 450g brush-top tin / 2kg / 5kg
A premium grade industrial anti-seize compound which is particularly suited for use on stainless steel components. Recommended for use where copper based products cannot be used e.g. where temperatures exceed 1100°C, where electrolytic corrosion occurs, in the presence of ammonia and for general use as an anti-seize agent on stainless steel or part stainless steel components. Temperature range -30C to +1425C.

SILVER GRADE ANTI-SEIZE - 20g / 50g / 450g

brush-top can / 2kg / 5kg / 20kg
A multi-purpose, high temperature lubricating compound, which combines graphite and fine metallic flakes in a non-melt grease base. Suitable for use on plastic, brass, copper, cast iron, steel and all alloys including stainless steel. Allows firmer tightening and easier opening of mating parts. Temperature range -30C to +870C.

SPRAY ADHESIVE 790 - 400g aerosol

A high strength, pressure sensitive contact adhesive which has been formulated for fast, strong bonding on a variety of surfaces. Typical applications include bonding aluminium foil, foam, wood, cardboard, paper, metal, fabric & textiles, most plastics, canvas, leather, rubber, cork, fibreglass and much more.

ZINC RICH COLD GAL - 400g / 500g aerosol

Used as a protective coating and/or primer wherever iron or steel will be exposed to corrosive conditions. The spray-film contains a high concentration of very fine particles of 98.5% pure zinc which acts as a sacrificial anode providing superior protection against corrosion.