



**Lube Control Pty Ltd**  
*Providing lubrication solutions!*

Unit 5/53 Norfolk Rd,  
Marion, SA 5043

t: (08) 8298 5563  
f: (08) 8298 6253  
e: info@lubecontrol.com.au

## ELECTRICALLY OPERATED OIL PUMPS 12V, 24V 240V

### 12V Operated Oil Transfer Pump

<p><b>12V Oil Pump, Gear, 30 LPM</b> <b>Part Number: P200-BV</b></p> <ul style="list-style-type: none"><li>• USA made by GPI 12v gear pump only. Suitable for medium viscosity oils such as 30 weight oil.*Do not use with petrol or diesel fuel. Up to 30 LPM with 30 weight oil at 15c or 20 weight oil at 4c.</li><li>• Duty Cycle: 30 min.</li><li>• Suction/Discharge/Total Lift: .7m/3.7m/5.3m</li><li>• Weight: 13kg</li><li>• Temp: -28c/+51c Inlet/outlet: 1" NPTF Draws 15.5A</li></ul>	
<p><b>12V Oil Pump - Gear, 10 LPM</b> <b>Part Number: 309010</b></p> <ul style="list-style-type: none"><li>• Gear pump; sintered steel gears. Noise levels less than 65dB. 10 LPM when pumping SAE30 oil. Hot oil up to 70c. Max viscosity: 600cSt</li><li>• Duty Cycle: 30 minutes on, 30 minutes off. 35 Amp.</li><li>• Weight: 4.9kg 3/4" BSPF ports. Max pressure: 5 bar . Integrated bypass.</li></ul>	

### 24V Operated Oil Transfer Pump

<p><b>24V Oil Pump - Gear, 10 LPM</b> <b>Part Number: 310010</b></p> <ul style="list-style-type: none"><li>• Gear pump; sintered steel gears. Noise levels less than 65dB. 10 LPM when pumping SAE30 oil. Hot oil up to 70c. Max viscosity: 600cSt</li><li>• Duty Cycle: 30 minutes on, 30 minutes off. 18 Amp.</li><li>• Weight: 4.9kg 3/4" BSPF ports Max pressure: 5 bar . Integrated bypass.</li></ul>	
--	---

## 240V Operated Oil Transfer Pump

<p><b>240V Oil Pump - Gear, 9 LPM</b>  <b>Part Number: 304100</b></p> <ul style="list-style-type: none"> <li>• Gear pump - 9 LPM when pumping SAE30 oil. Hot oil up to 70c. 1" BSPF inlet/outlet. Weight: 9kg.</li> <li>• Max pressure: 160psi.</li> <li>• 240V, 50Hz; 1450 rpm, 550w.</li> <li>• Integrated bypass.</li> </ul>	
<p><b>240V Oil Pump - Vane, 25 LPM</b>  <b>Part Number: 334900</b></p> <ul style="list-style-type: none"> <li>• Vane pump for continuous operation; sintered steel rotor with resin vanes. Noise levels less than 70dB.</li> <li>• 25 LPM when pumping SAE30 oil. Hot oil up to 70c.</li> <li>• Weight: 14.2kg.</li> <li>• Max pressure: 6 bar 750 watt; 1450 rpm. Integrated bypass. 3/4" BSPF ports.</li> </ul>	
<p><b>240V Oil Pump - 50 LPM, Stationary</b>  <b>Part Number: 305200</b></p> <ul style="list-style-type: none"> <li>• 1.5Kw 240vac heavy duty gear pump &amp; motor capable of flow rates up to 50 LPM free flow. Can pump SAE30 oil through hose reels.</li> <li>• Includes thermal protection &amp; recirculation bypass</li> <li>• Inlet/outlet: 1" BSPF Max op pressure: 150 psi</li> <li>• Weight: 35Kg Dimensions: 600Lx400Hx350W mm</li> </ul>	
<p><b>240V Oil Pump - 65 LPM, 1" Outlet</b>  <b>Part Number: 65EA</b></p> <ul style="list-style-type: none"> <li>• 65 LPM when pumping SAE30 oil, free flow.</li> <li>• Motor: 3 HP self ventilated w/ recirculation bypass. IP55. Pressure: 8kg/cm2.</li> <li>• Suction: 2.5 mtrs. Delivery: up to 60 mtrs. Inlet/outlet: 1" BSPF.</li> <li>• *Requires 15 amp fuse.</li> </ul>	

## Oil Transfer Kits 12V and 24V

<p><b>Piusi 12V Oil Transfer Kit with on/off Gun</b>  <b>Part Number: 309060</b></p> <ul style="list-style-type: none"> <li>• Flow rates of up to 10LPM</li> <li>• Self-priming rotary vane pump</li> <li>• Supplied inclusive of a 2-metre battery connection cable with clips, 4-metre 3/4" diam. oil delivery hose, on/off control valve and intake hose filter.</li> <li>• Duty cycle of 30 minutes on &amp; 30 minutes off</li> </ul>	
<p><b>Piusi 24V Oil Transfer Kit with on/off Gun</b>  <b>Part Number: 310070</b></p> <ul style="list-style-type: none"> <li>• Flow rates of up to 10LPM</li> <li>• Self-priming rotary vane pump</li> <li>• Supplied inclusive of a 2-metre battery connection cable with clips, 4-metre 3/4" diam. oil delivery hose, on/off control valve and intake hose filter.</li> <li>• Duty cycle of 30 minutes on &amp; 30 minutes off</li> </ul>	