

IMPORTED AND DISTRIBUTED BY MACNAUGHT PTY LTD

**lubemate** 



**lubemate** 

CATALOGUE

# SUMMARY

Lubemate represents an exciting new era in consumer choice in lubrication equipment.

This new line of fully imported products is designed to offer real value to the Australian market.

- Fully imported
- Benchmark value
- 12 month replacement warranty

Lubemate is the value choice for the casual consumer.

# CONTENTS

<b>HAND OPERATED GREASING EQUIPMENT</b>	<b>1-2</b>
<b>HAND OPERATED PUMPING EQUIPMENT</b>	<b>3</b>
<b>FUEL TRANSFER EQUIPMENT</b>	<b>4</b>
<b>OIL CONTROL GUNS</b>	<b>5</b>
<b>OIL DRAINERS/EXTRACTORS</b>	<b>5</b>
<b>METAL/PLASTIC REELS</b>	<b>6</b>
<b>AIR OPERATED PUMPING EQUIPMENT</b>	<b>6</b>
<b>AIR OPERATED GREASING EQUIPMENT</b>	<b>7</b>
<b>DOUBLE DIAPHRAGM PUMPS</b>	<b>7</b>
<b>CHEMICAL PUMPS</b>	<b>8</b>
<b>PLASTIC JUGS &amp; FUNNELS</b>	<b>8</b>

# WARRANTY

1. Macnaught Pty Ltd ("Macnaught") warrants that all products supplied by Macnaught under the "Lubemate" brand will be free from any defects caused by faulty materials or workmanship ("Warranty") for a period of 12 months from the date of purchase of the product.
2. The warranty is conditional on the purchaser, during the Warranty period:
  - a. delivering to Macnaught a detailed notice setting out full details of any defect in any product and details of the date and place of purchase (together with copies of purchase receipts and/or other supporting documents); and
  - b. at the purchaser's own cost, returning the defective product to Macnaught.
3. Subject to compliance by the purchaser with clause 2, Macnaught shall replace any product found defective by its inspection by reason of faulty materials or workmanship.
4. This Warranty does not cover the failure of products, parts or components which, in the sole judgment of Macnaught, arises other than from faulty materials or workmanship, including misuse, abrasion, corrosion, negligence, accident, unauthorised modification, improper use, storage or handling, faulty installation or tampering by the purchaser or any third party.
5. If Macnaught's inspection discloses no defect in material or workmanship, the product will be returned to the purchaser at customary charges, which will be advised to the purchaser.
6. Macnaught's liability and the purchaser's rights under this Warranty shall be limited to the replacement of defective products and in particular, shall not extend to any direct, special, indirect or consequential damage or losses of any nature.
7. The foregoing Warranty supersedes, voids and is in lieu of all or any other warranties.

This Warranty does not form part of, nor does it constitute, a contract between Macnaught and the end-user or purchaser. It is additional to any warranty given by the seller of the products. This Warranty does not exclude, limit, restrict or modify the non-excludable rights or remedies conferred upon the end-user or purchaser, or the non-excludable duties or liabilities imposed on the seller or Macnaught, by Part V, Divisions 2, 2A and Part VA of the Trade Practices Act 1974 (Commonwealth) or other legislative provisions. Macnaught otherwise excludes, to the extent permitted by law, any rights conferred on the end-user or purchaser or duties or liabilities imposed upon Macnaught.

# HAND OPERATED GREASING EQUIPMENT



## LEVER GREASE GUN

### L-LG450

Heavy Duty Lever Action Grease Gun for use with 450g Grease Cartridge, bulk or suction fill. Fitted with bulk loader and air release valve. Complete with 300mm High Pressure Hose, 150mm steel extension & coupler. Develops 69,000 kPa (10,000 psi)

## ECONOMY LEVER GREASE GUN

### L-LG450E

Standard Lever Action Grease Gun for use with 450g Grease Cartridge, bulk or suction fill. Fitted with bulk loader. Complete with 150mm steel extension & coupler. Develops 41 400 kPa (6,000 psi)



## PRESSURE/VOLUME PISTOL GREASE GUN

### L-PG450PV

Pistol Grip Grease Gun with variable high pressure/high volume settings for use with 450g Grease Cartridge, bulk or suction fill. Fitted with bulk loader. Complete with 300mm High Pressure Hose & coupler. Develops 48 300 kPa (7,000 psi) in high pressure setting



## MINI PISTOL GREASE GUN

### L-MPG

Mini Pistol Grease Gun for use with 3 oz. Grease Cartridge or suction fill. Complete with 100mm steel extension & coupler. Develops 24 000 kPa (3,500 psi)



## PISTOL GREASE GUN

### L-PG450

Pistol Grip Grease Gun for use with 450g Grease Cartridge or suction fill. Fitted with steel block nut. Complete with 300mm High Pressure Hose, 100mm steel extension & coupler. Develops 34 500 kPa (5,000 psi)



# HAND OPERATED GREASING EQUIPMENT [CONT]



## AIR OPERATED GREASE GUN

### L-AG450

Continuous Action Air Operated Grease gun for use with 450g Grease Cartridge, bulk or suction fill. Fitted with bulk loader. Complete with 300mm High Pressure Hose & coupler. Develops 33 100 kPa (4,800 psi)

## 18V BATTERY GREASE GUN

### L-BG18V

18 volt Battery Operated Grease Gun for use with 450g Grease Cartridge or suction fill. Fitted with block nut and air release valve. Complete with 1000mm High Pressure Hose & coupler, Battery Charger, spare Battery and shoulder strap. Develops 51 700 kPa (7,500 psi) and delivers 50g/min



## 4 JAW COUPLER

### L-C4

4 Jaw Coupler with Ball Check. 1/8" BSPT



## 20KG GREASE PUMP

### L-GP20

Grease Filler Pump for 20kg grease pails. Complete with drum cover and rubber follower plate



## FLEX EXTENSION 300MM/450MM

### L-FX12

300 mm High Pressure Hose. 1/8" BSPT. WP 40 000 kPa (5,800 PSI) , BP 95 000 kPa (13,775 PSI)



### L-FX18

450 mm High Pressure Hose. 1/8" BSPT. WP 40 000 kPa (5,800 PSI) , BP 95 000 kPa (13,775 PSI)

## GREASE GUN HOLDER

### L-GGH

Grease Gun Holder for 450 g barrels (63 mm dia)



# HAND OPERATED PUMPING EQUIPMENT



## PLASTIC 20L DRUM PUMP

### L-DP20

Hand Pump for 20L drums with 1200mm of PVC hose with spring. Pump length 325mm. Includes 2 bung adaptors for metal & plastic drums, an additional Rieke Adaptor and pump length extender

## LEVER BARREL PUMP

### L-LBP

Lever action Barrel Pump complete with telescopic Suction Tube, 1.1/2" & 2" bung adaptors. Fits 60- 205L drums. Complete with Hose Assembly



## TOP UP PUMP 1L BOTTLE

### L-TUP1L

Top-up Pump. 1L bottle



## ROTARY VANE PUMP WITH HOSE

### L-RPH

Rotary Hand Pump with 1" Inlet. Heavy duty cast iron construction, dual directional operation. Complete with 2" bung nut & 3 piece suction tube for use on 60 - 205L drums. Complete with Hose Assembly. Dispenses 5L per 20 turns



## OIL CAN 300ML

### L-OC300

Oil Can. 300mL with Steel Pump. Complete with Rigid & Flexible Spout



## BI-LOBE PUMP WITH HOSE

### L-BLPH

High Flow Rotary Bi-Lobe Pump. 100L/min. Complete with 2 piece suction tube and strainer, 2m delivery hose, delivery nozzle and nozzle holder.



## PLASTIC SYPHON PUMP

### L-PSP

Polyethylene Heavy Duty Siphon pump for use with water based fluids, detergents, waxes, soaps, antifreeze etc. For use with 205L drums. Dispenses 21 L/min



## DRUM TROLLEY 20L/60L

### L-DT2060

Drum trolley suitable for 20L to 60L drums



## SUCTION GUN

### L-SG500

Suction Gun with 300mm hose. 500mL capacity



## ALUMINIUM DRUM WRENCH

### L-DWA

Aluminium Drum Wrench for 2" and 3/4" drum plugs



# FUEL TRANSFER EQUIPMENT



## 12V ELECTRIC DIESEL PUMP - MANUAL NOZZLE

### L-FPM12V

12V Electric Diesel Pump with Manual Nozzle. Flow rate 60 L/min (free flow). 4m delivery hose. 2m suction hose with check valve

## 12V ELECTRIC DIESEL PUMP - AUTO NOZZLE

### L-FPA12V

12V Electric Diesel Pump with Auto Nozzle. Flow rate 60 L/min (free flow). 4m delivery hose. 2m suction hose with check valve



## MANUAL DIESEL NOZZLE

### L-FNMD

Manual Fuel Nozzle. 1" BSP inlet. 15/16" spout



## AUTO ULP NOZZLE

### L-FNAU

Auto Shut-off Fuel Nozzle. 3/4" BSP inlet. 13/16" spout



## SWIVEL 3/4"

### L-FS19

3/4" M to 3/4" F Swivel to suit auto nozzle



## AUTO DIESEL NOZZLE

### L-FNAD

Auto Shut-off Fuel Nozzle. 3/4" BSP inlet. 15/16" spout



## SWIVEL 1"

### L-FS25

1" M to 1" F Swivel to suit manual nozzle



## MANUAL ULP NOZZLE

### L-FNMU

Manual Fuel Nozzle. 1" BSP inlet. 13/16" spout



## FUEL METER 1"

### L-FM25

Fuel Meter. Flow rate 20 - 120 L/min. Max. operating pressure 345 kPa (50 psi). 1" BSP





# OIL CONTROL GUNS

# OIL DRAINERS/ EXTRACTORS

## OIL CONTROL VALVE RIGID EXTENSION

### L-OCVR

Oil Control Valve with rigid extension and auto non-drip nozzle. 20 L/min. Working Pressure 5000 kPa (700psi)



## OIL CONTROL VALVE FLEX EXTENSION

### L-OCVF

Oil Control Valve with flexible extension and auto non-drip nozzle. 20 L/min. Working pressure 5000 kPa (700psi)



## ELECTRONIC HEG RIGID EXTENSION

### L-ECVR

Electronic Oil Control Valve with rigid extension and auto non-drip nozzle. 20 L/min. Working pressure 5000 kPa (700psi). Accuracy +/- 0.5%. Temperature range -10°C to +60°C



## ELECTRONIC HEG FLEX EXTENSION

### L-ECVF

Electronic Oil Control Valve with flexible extension and auto non-drip nozzle. 20 L/min. Working pressure 5000 kPa (700psi). Accuracy +/- 0.5%. Temperature range -10°C to +60°C



## 6.5L WASTE OIL EXTRACTOR

### L-OE6

Manual Oil Extractor. 6.5 L capacity



## 80L WASTE OIL DRAINER

### L-OD80

80 L gravity fed Oil Drainer



## 80L WASTE OIL DRAINER WITH CHAMBER

### L-OES89

80 L Oil Evacuation System complete with recovery basin, 9L pre-fill chamber, metal and flexible probes. Can be used as standard gravity oil sump basin or as an air evacuation system



# METAL/PLASTIC REELS

# AIR OPERATED PUMPING EQUIPMENT

## METAL GREASE REEL 6MM X 15M

### L-MG0615

Metal Grease Reel supplied with 15 m x 6 mm ID SAE 100 R2 rubber hose. Operating pressure up to 34 500 kPa (5,000 psi). ¼" BSP (F) reel inlet, ¼" BSP (M) hose outlet



## 1:1 DRUM PUMP 205L

### L-ARPD1

1:1 Pump for 205 L Drums



## METAL AIR/WATER REEL 12MM X 15M

### L-MAW1215

Metal Air/Water Reel supplied with 15 m x 12.5 mm ID rubber hose. Operating pressure up to 2100 Kpa (300 psi). ½" BSP (F) reel inlet, ½" BSP (M) hose outlet



## 1:1 STUB PUMP

### L-ARPS1

1:1 Pump , Stub



## METAL OIL REEL 12MM X 15M

### L-MO1215

Metal Oil Reel supplied with 15 m x 12.5 mm ID SAE 100 R1 rubber hose. Operating pressure up to 6900 kPa (1,000 psi). ½" BSP (F) reel inlet, ½" BSP (M) hose outlet



## 3:1 DRUM PUMP 205L

### L-ARPD3

3:1 Pump for 205 L Drums



## PLASTIC AIR/WATER REEL 10MM X 15M

### L-PAW1015

Plastic Reel for Air/Water. 10mm x 15m hose. Working Pressure 1700 kPa (250psi)



## 3:1 STUB PUMP

### L-ARPS3

3:1 Pump , Stub



## PLASTIC AIR/WATER REEL 12MM X 15M

### L-PAW1215

Plastic Reel for Air/Water. 12mm x 15m hose. Working Pressure 1700 kPa (250psi)



## 5:1 DRUM PUMP 205L

### L-ARPD5

5:1 Pump for 205 L Drums



## 5:1 STUB PUMP

### L-ARPS5

5:1 Pump , Stub



# AIR OPERATED GREASING EQUIPMENT

# DOUBLE DIAPHRAGM PUMPS

## AIR OPERATED GREASING KIT 20/180KG DRUM

**L-GK20** 50:1 Grease Ratio Pump, for use with 20 to 30kg grease drums. Air Inlet 1/4" F, Pump Outlet 1/4" F. Working pressure 1000 kPa (150 psi). Complete with 2.1m high pressure hose, Z Swivel, control valve, drum cover & follower plate

**L-GK180** As above. For use with 180kg drums



## 50:1 GREASE PUMP 180KG DRUM

### L-ARPG50

50:1 Grease Ratio Pump only for 180 kg Grease Drums



## LID 20KG/180KG

### L-L20

Drum Cover Assembly for 20 kg Air Operated Grease Pump

### L-L180

Drum Cover Assembly for 180 kg Air Operated Grease Pump



## FOLLOWER 20KG/180KG

### L-F20

Rubber Lining Follower Plate for 20 kg Grease Drums

### L-F180

Rubber Lining Follower Plate for 180 kg Grease Drums



## GREASE CONTROL VALVE

### L-GCV

Grease Control Valve , 51 700 kPa (7,500 psi) , inlet 1/4" BSPT (F). Supplied complete with 150mm steel extension & coupler



## Z-SWIVEL

### L-ZS

1/4" BSPT (Female) x 1/4" BSPT (Male)



## 1/2" DIAPHRAGM PUMP PP

### L-DDP13

Double Diaphragm Pump. Polypropylene construction. Flow Rate 53 L/min. 1/2" NPT connections



## 3/4" DIAPHRAGM PUMP AL/PP

### L-DDP19

Double Diaphragm Pump. Aluminium and polypropylene construction. Flow rate 53 L/min. 3/4" NPT connections



## 1" DIAPHRAGM PUMP AL/PP

### L-DDP25

Double Diaphragm Pump. Aluminium and polypropylene construction. Flow rate 140 L/min. 1" BSP connections



# CHEMICAL PUMPS

# PLASTIC JUGS & FUNNELS

## ROTARY VANE CHEMICAL PUMP - PP

### L-RPCP

Rotary Chemical Pump with polypropylene pump body & vanes, Viton seals & steel hardware. Complete with bung with 2" external threads & 3 piece threaded suction tube. For dispensing oil based media



## ROTARY VANE CHEMICAL PUMP - RYTON

### L-RPCR

Rotary Chemical Pump with glass filled polypropylene construction, Ryton vanes, Viton seals & stainless steel hardware. Complete with bung with 2" external threads & 2 piece threaded suction tube. For dispensing water based media, antifreeze, acids and chemicals



## STAINLESS STEEL DRUM PUMP

### L-SSHP

Stainless Steel Drum Pump suitable for 60/205L drums. Delivers approx. 400 ml per stroke



## JUG 2L/5L

### L-J2L

2.0 L Measuring Jug

### L-J5L

5.0 L Measuring Jug



## ANTI SPILL FUNNEL SMALL/LARGE

### L-ASFS

Small. Capacity 1.7 L. 200mm dia.

### L-ASFL

Large. Capacity 3.0 L. 240 mm dia. Supplied complete with drum bung

