

greasing equipment - air operated

maxilube®

P8

The P8 MAXILUBE® is a larger version of the P6, designed to fit 180 kg (400 lbs) grease containers.

Features - P8-01 Pump only

- quiet, non-corroding air motor
- low air consumption
- no air line lubricator required

Features - P8-11 Complete system

- drum lid
- rubber edged follower plate with built-in release valve and removal system
- 2.5 m (8 ft.) x 6 mm (1/4") ID delivery hose
- B2 booster gun with 360° ZSB swivel
- fully serviceable
- 10 year warranty and parts guarantee

Specifications

- grease viscosity:
up to NLGI No.2
- wetted components:
zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- output:
approx. 460 g/min (16 oz/min)
- min. air pressure:
400 kPa (60 psi, 4 bar)
- min. compressor size:
0.08 m3/min (3 cfm)
- air inlet:
1/4" NPT (F)
- pump outlet:
1/4" NPT (F)
- pump ratio:
50:1 (grease pressure is 50 times air pressure)
- B2 gun pressure:
up to 69 000 kPa (10 000 psi, 690 bar)
- hose thread:
1/4" NPT (M)



P8-01



Accessories

- PDF21 Push On Extension
- ACK2 Aviation Kit
- MCFK1 All-purpose Air Greasing Kit
- TR205 Trolley