oil transfer equipment - air operated

oilmaster[®] ratio oil pumps

T112

Transfer oils up to 10 metres (33 ft) with this 1:1 ratio stub pump. Designed for inclusion in a workshop or mobile bulk oil transfer system and can be used with Macnaught's range of oil control guns.

Features

| • | quiet, non-corroding air motor | |
|----------------|--------------------------------------|--|
| • | low air consumption | |
| • | 2" (M) bung adaptor | |
| • | no air line lubricator required | |
| • | fully serviceable | |
| • | 10 year warranty and parts guarantee | |
| Specifications | | |

| • co | mpatible fluids: | oils up to SAE 140, automatic transmission fluid, engine oil, gear oil and hydraulic oils |
|-------|---------------------|---|
| • we | etted components: | aluminium, zinc and hard chrome plated carbon steel, brass, nitrile and polyurethane rubber |
| • pı | Imp ratio: | 1:1 (oil pressure is the same as air pressure) |
| • OL | itput: | 27 L/min (7 US gal/min) of SAE 10 oil at 690 kPa (100 psi) air pressure (free flow) |
| • m | ax. air pressure: | 1 030 kPa (150 psi, 10.3 bar) |
| • m | in. air pressure: | 400 kPa (60 psi, 4 bar) |
| • m | in. air compressor: | 0.3 m3/min, (10 cfm) |
| • air | r inlet: | 1/4" NPT (F) |
| • pi | ımp inlet: | 1" BSP or NPT (F) and 1" UNEF |
| • pi | imp outlet: | 3⁄4″ BSP or NPT (F) |

Accessories

• TB25S or TB26S Telescopic Suction Tube

INNOVATIO

- TD20 Wall Bracket
- TA-4K Pressure Regulator Kit





CELEBRATING Macnaught USA Macnaught USA, Inc. 614 South Ware Boulevard Dock 14A (for deliveries) Tampa, FL 33619 P: 813-628-5506 F: 509-694-8495 E: info@macnaughtusa.com W: www.macnaughtusa.com



| Fluid | Free flow (per min.) at pump outlet | Output (per min.) through 3 m (10 ft) x 19 mm (34") hose, and hose end oil delivery gun |
|------------|-------------------------------------|--|
| | Litres US Gal | Litres US Gal |
| Oil SAE 10 | 27 7.1 | 10 2.6 |
| Oil SAE 30 | 23 6.1 | 8.5 2.2 |
| Oil SAE 90 | 22 5.8 | 7 1.8 |

*flow rates are a guide only and any variations can depend on system setup *flow rates at 690 kPa (100 psi) air pressure

Macnaught Europe Macnaught Europe Ltd D1 Lincoln Park Borough Road Buckingham Road Ind Est Brackley NN13 7BE United Kingdom P: +44 1280 705001 F: +44 1280 705006 E: info@macnaughteurope.com W: www.macnaughteurope.com



oil transfer equipment - air operated

oilmaster[®] ratio oil pumps

T312

Transfer oils up to 30 metres (98 ft) with this 3:1 ratio pump. Designed for inclusion in a workshop or mobile bulk oil system and can be used with Macnaught's range of oil control guns and hose reels.

Features

| • | quiet, non-corroding air motor | |
|---|--------------------------------------|--|
| • | low air consumption | |
| • | 2" (M) bung adaptor supplied | |
| • | no air line lubricator required | |
| • | built-in pressure relief valve | |
| • | fully serviceable | |
| • | 10 year warranty and parts guarantee | |
| | | |

Specifications

| • | compatible fluids: | oils up to SAE 140, automatic transmission fluid, engine oil, gear oil and hydraulic oils |
|---|--------------------|---|
| • | wetted components: | aluminium, zinc and hard chrome plated carbon steel, brass, nitrile and polyurethane rubber |
| • | pump ratio: | 3:1 (oil pressure is 3 times the air pressure) |
| • | output: | 15 L/min (4 US gal/min) of SAE 10 oil at 690 kPa (100 psi) air pressure (free flow) |
| • | max. air pressure: | 1 030 kPa (150 psi, 10.3 bar) |
| • | min. air pressure: | 400 kPa (60 psi, 4 bar) |
| • | air inlet: | 1/4" NPT (F) |
| • | pump inlet: | 1" BSP or NPT (F) and 1" UNEF |
| • | pump outlet: | 3⁄4″ BSP or NPT (F) |

Accessories

- TB25S or TB26S Telescopic Suction Tube
- TD20 Wall Bracket
- TA-7K Filter & Regulator Kit
- TD-25K Oil Feeder Hose



Head Office - Sydney Macnaught Pty Ltd 41-49 Henderson St, Turrella Sydney NSW 2205 Australia P: +61-2-9567 0401 F: +61-2-9597 7773 E: info@macnaught.com.au W: www.macnaught.com.au CELEBRATING Macnaught USA, Inc. 614 South Ware Boulevard Dock 14A (for deliveries) Tampa, FL 33619 P: 813-628-5506 F: 509-694-8495 E: info@macnaughtusa.com W: www.macnaughtusa.com



| Fluid | Free flow (per min) at pump outlet | Output (per min) through 3m (30 ft) x 12.5 mm (1/2') hose,10 m (33 ft) x 12.5 mm |
|------------|------------------------------------|--|
| | | (1/2") hose reel and |
| | | oil control gun |
| | Litres US Gal | Litres US Gal |
| Oil SAE 10 | 15 4 | 10 2.6 |
| Oil SAE 30 | 13 3.4 | 7 1.8 |
| Oil SAE 90 | 10 2.6 | 6 1.6 |
| | | |

*flow rates are a guide only and any variations can depend on system setup *flow rates at 690 kPa (100 psi) air pressure

Macnaught Europe Macnaught Europe Ltd D1 Lincoln Park Borough Road Buckingham Road Ind Est Brackley NN13 7BE United Kingdom P: +44 1280 705001 F: +44 1280 705006 E: info@macnaughteurope.com W: www.macnaughteurope.com

