

Pitot Tube Sampling Ports

Trico's Pitot Tube sampling ports are designed to provide a safe, simple and effective method of sampling fluids from sumps and non-flooded horizontal drain lines. They ensure oil samples are drawn from the most appropriate location of the sump reservoir, and that the sample is taken from the exact location inside the system each time, which is important for maintaining consistency in routine sampling. The thick wall tubing can be bent and directed to the ideal sampling location with the use of a swivel adapter.

FEATURES:


- Pitot Tubes are equipped with sample ports.
- Available in 12", 18", 24" and 72" lengths.
- Installs easily into drain, fill or sampling pipe ports.
- Swivel options available for bent tubes in confined locations.

SPECIFICATIONS

Maximum Pressure	500 PSI (34.5 bar)	
Material	Carbon Steel or Stainless Steel	
Check Valve Ball	Stainless Steel	
Seal	Viton	
Maximum Operating Temperature	-4°F to 392°F	

CARBON STEEL SAMPLE PORT AND TUBE

Fixed Adapter	Swivel Adapter	Tube Length	Fitting
36200	36213	12"	1/4" NPT Male
36201	36214	18"	1/4" NPT Male
36202	36215	24"	1/4" NPT Male
36203	36216	72"	1/4" NPT Male



CARBON STEEL SAMPLE PORT AND STAINLESS STEEL TUBE

Fixed Adapter	Swivel Adapter	Tube Length	Fitting
36204	36217	12"	1/4" NPT Male
36207	36220	18"	1/4" NPT Male
36210	36223	24"	1/4" NPT Male



STAINLESS STEEL SAMPLE PORT AND CARBON STEEL TUBE

Fixed Adapter	Swivel Adapter	Tube Length	Fitting
36205	36218	12"	1/4" NPT Male
36208	36221	18"	1/4" NPT Male
36211	36224	24"	1/4" NPT Male

STAINLESS STEEL SAMPLE PORT AND TUBE

Fixed Adapter	Swivel Adapter	Tube Length	Fitting
36206	36219	12"	1/4" NPT Male
36209	36222	18"	1/4" NPT Male
36212	36225	24"	1/4" NPT Male



LUBE Control

Lube Control Pty Ltd

Providing lubrication solutions!

Unit 5/53 Norfolk Rd,
Marion, SA 5043
t: (08) 8298 5563
f: (08) 8298 6253
e: info@lubecontrol.com.au

www.lubecontrol.com.au