

# VISCOTROLL AC *The Original*



## Mobile unit for oil transfer

Viscotroll is the ideal product for delivering oil from a drum anywhere in the workshop. As it is powered by electricity it can be connected to any power socket thus eliminating the need for compressed air.

The group comes equipped with a self-priming gear pump. The nozzle is installed with a flow meter and display to guarantee precise delivery operations, giving total control over the fluid used.

### Performances

- Flow rate 25 l/min (6,6 gal/min).
- Operating pressure 6 bar (85 psi).
- Noise levels less than 65 dB.
- Oil viscosity from 10 to 500 "cSt".
- K33 meter with accuracy +/- 1%.

### Specifications

- Tubular structure trailer-mounted support for moving drums, complete with nozzle support, pipe support and drip collector.

collector.

- Self-priming pump with a.c. asynchronous motor, self-ventilating closed (protection rating IP 55) at 230 V.
- 1" BSP suction pipe with standing valve and filter.
- 4 metre long 3/4 " BSP delivery pipe
- Delivery nozzle.

### Options:

- Flow meter.
- Pressure switch with incorporated safety valve.

Available: **UREA versions.**




## VISCOTROLL 70

Flow rate **25** l/min

Accuracy +/- **1%**

Viscosity up to **500** cSt



**VANE**



Viscotroll is without drum

## VISCOTROLL 200

Flow rate up to **9** l/min

Accuracy ± **0,5 %**

Viscosity up to **2000** cSt



**GEAR**



Code	Description		Flow rate		AC			Meter	Nozzle	Pump mod.	Viscosity cSt max	Weight Kg	Packaging mm
			l/min	gal/min	Tension V	Freq. Hz	Power Watt						
000263100	Viscotroll 70		25	6,6	230	50	750	-	S3000	Viscomat	500	34	1090x690x300
000263110	Viscotroll 70/K33		25	6,6	230	50	750	K33	S3000	Viscomat	500	36	1090x690x300
F0026300D	Viscotroll 200/2 AC		9	2,4	230	50	750	-	Easyoil	Viscomat	500	34	1090x690x300
F0026301D	Viscotroll 200/2 AC - K400		9	2,4	230	50	750	K400	Easyoil	Viscomat	500	35	1090x690x300
00026302D	Viscotroll 200/2 AC - PST		9	2,4	230	50	750	-	Easyoil	Viscomat	500	36	1090x690x300
00026303D	Viscotroll 200/2 AC - PST - K400		9	2,4	230	50	750	K400	Easyoil	Viscomat	500	37	1090x690x300

Upon request it is available with different voltage and frequency

